

August 2005

Woodgard

PRODUCT INFORMATION

WOODGARD FLOORGARD

G 684-1436

PRODUCT BENEFITS

- FLOORGARD dries to an extremely hard abrasion-resistant finish, which resists scratch marks.
- A non-yellowing crystal clear sealer for wooden floors and interior wood work.
- A low odour varnish with excellent flow properties.
- FLOORGARD represents the practical way of finishing interior wooden floors and woodwork.
- It is a time and money saver. Easy to clean, makes polishing obsolete.
- Dries to a beautiful gloss finish - looks and feels like a waxed surface and highlights the natural grain.
- Seals wooden floors and woodwork.
- Resists household cleaning materials and beverage stains.

USES

As a finish for all types of interior wooden flooring where a hard wearing, slip resistant coating is required.

Also recommended as an interior finish for wooden doors and panelling where a particularly scratch and mar resistant clear coat that is non-yellowing is required.

GENERAL DATA

Type	Water-based Acrylic Polyurethane Clear Varnish
Drying Time @ 25 °C	Touch Dry 30 minutes
Recoating Time	4 hours
Through Dry	24 hrs (Complete cure 5days at 23°C and 60% Humidity)
Solids Content	30-32% (W/W %)
Spreading Rate	10-12 m ² per litre depending on surface porosity
Number of Coats	3-4 coats depending on substrate

COLOUR RANGE

- Clear in a gloss finish

APPLICATION

Apply by **Brush or Roller**

- **Do not thin-** the product is ready for use.
- Stir well before use. Keep the container tightly closed after use.
- During application and drying the temperature must be above 5°C and relative humidity below 80%.
- Woodgard FLOORGARD will look milky when being applied, but it will dry to a clear film.

SURFACE PREPARATION

The substrate must be dry, clean and sound, with varnishing only to commence above 5°C.

NEW SURFACES

- Sand the floor smooth with power sander. Then vacuum to remove dust.
- It is advisable to apply a "test piece" to new parquet floors, which have been bonded with bitumen, to ensure that the FLOORGARD will harden.
- Apply 1-2 coats of Woodgard FLOORGARD, light sanding and then apply a further 2 coats of Woodgard FLOORGARD.

PREVIOUSLY PAINTED SURFACES OR OLD FLOORS

- Remove wax or polish by power sanding. It is not sufficient to wash floors with paraffin, as any residual polish will interfere with the adhesion of FLOORGARD.
- Painted or lacquered floors, or floors treated with conventional varnishes must also be sanded to a matt surface and cleaned.
- It is recommended that a small test area be painted on old varnish, before coating the whole area.
- Apply 1-2 coats of Woodgard FLOORGARD, sand lightly, and then apply a further 2 coats of Woodgard FLOORGARD.

CLEANING OF TOOLS

- Wash with soap and water.

PRECAUTIONS

- For detailed safety information refer to the Material Safety Data Sheet G684-1436.
- Do not apply during wet weather. This could turn the FLOORGARD milky and in extreme cases, white.
- Do not smoke and avoid inhaling the fumes of FLOORGARD.
- Ventilate area after application.

FLASH POINT

>60°C